

Arduino MEGA2560

Produktkode: 243aa

Tilgjengelighet: 5

Pris: kr. 80,00

Short Description

MEGA2560 R3 Board ATmega2560-16AU CH340G + Free USB Cable for Arduino

Beskrivelse

Disse enhetene er brukte, men fungerer som nye. Selges til redusert pris i utgangspunktet.

[Arduino beskrivelse](#)

Overview

This is the new **MEGA2560 R3**. In addition to all the features of the previous board, the MEGA now uses an ATmega16U2 instead of the ATmega8U2 chip. This allows for faster transfer rates and more memory. No drivers needed for Linux or Mac (inf file for Windows is needed and included in the Arduino IDE), and the ability to have the Uno show up as a keyboard, mouse, joystick, etc.

The MEGA2560 R3 also adds **SDA** and **SCL** pins next to the AREF. In addition, there are two new pins placed near the RESET pin. One is the IOREF that allow the shields to adapt to the voltage provided from the board. The other is a not connected and is reserved for future purposes. The MEGA2560 R3 works with all existing shields but can adapt to new shields which use these additional pins.

Revision 3 of the board has the following new features:

1.0 pinout: added **SDA** and **SCL** pins that are near to the AREF pin and two other new pins placed near to the RESET pin, the IOREF that allow the shields to adapt to the voltage provided from the board. In future, shields will be compatible both with the board that use the AVR, which operate with 5V and with the Arduino Due that operate with 3.3V. The second one is a not connected pin, that is reserved for future purposes.
Stronger RESET circuit.

Atmega 16U2 replace the 8U2.

Description

Microcontroller	ATmega2560
Operating Voltage	5V
Input Voltage (recommended)	7-12V
Input Voltage (limits)	6-20V
Digital I/O Pins	54 (of which 15 provide PWM output)
Analog Input Pins	16
DC Current per I/O Pin	40 mA
DC Current for 3.3V Pin	50 mA
Flash Memory	256 KB of which 8 KB used by bootloader
SRAM	8 KB
EEPROM	4 KB
Clock Speed	16 MHz

Package List

1X Mega2560 R3 2013 Version For Arduino Compatible

1X USB Cable

Pinout

[Lenke](#)

POWER	DEFAULT
GND	TIMER
DIGITAL PIN	ANALOG
ANALOG PIN	INTERRUPT
COMMUNICATION	OTHER
MICROCONTROLLER PIN	SWD
INTERNAL	

ICSP1		ATMEGA16U2	
1	MISO	PB3	
2	+5V	PB1	
3	SCK	PB2	
4	MOSI	PC1	
5	RESET		
6	GND		

