

LM339

Produktkode: 596aa

Tilgjengelighet: 21

Lager : S48a

Ring/SMS etter pris: 91166668



Short Description

LM339N LM339 Low Power Quad Voltage Comparators New IC

Beskrivelse

Description:

The LM339 devices consist of four independent voltage comparators that are designed to operate from a single power supply over a wide range of voltages. Operation from dual supplies also is possible, as long as the difference between the two supplies is 2 V to 36 V, and V_{CC} is at least 1.5 V more positive than the input common-mode voltage. Current drain is independent of the supply voltage. The outputs can be connected to other open-collector outputs to achieve wired-AND relationships.

Included:

- 5 x LM339N

This item features:

- Wide Supply Ranges

- Single Supply: 2 V to 36 V
(Tested to 30 V for Non-V Devices and
32 V for V-Suffix Devices)
- Dual Supplies: 11 V to 118 V
(Tested to 115 V for Non-V Devices and
116 V for V-Suffix Devices)
- Low Supply-Current Drain Independent of
Supply Voltage: 0.8 mA (Typical)
- Low Input Bias Current: 25 nA (Typical)
- Low Input Offset Current: 3 nA (Typical) (LM139)
- Low Input Offset Voltage: 2 mV (Typical)
- Common-Mode Input Voltage Range
Includes Ground
- Differential Input Voltage Range Equal to Maximum-Rated Supply Voltage:
136 V
- Low Output Saturation Voltage
- Output Compatible With TTL, MOS, and CMOS
- On Products Compliant to MIL-PRF-38535,
All Parameters Are Tested Unless Otherwise Noted. On All Other Products,
Production Processing Does Not Necessarily Include Testing of All Parameters.