WouXun Kg-UV950p Dual Band Car Mobile Radio Communicator CB VHF/UHF Amateur



Produktkode: 379aa
Tilgjengelighet: Opp til 1 mnd leveringstid
Weight: 1,260.00g

Pris: kr. 4.500,00

Kort beskrivelse
WouXun Kg-UV950p Dual Band Car Mobile Radio Communicator CB VHF/UHF Amateur

Beskrivelse
Hot spots

1.999 memory channel

2. Dual Display

3.8 groups scrambler

4.Band can be set freely(V/U U/V V/V U/U)

Product introduction

Frequency range

RX:26.000-29.995MHz and 50.000-53.995MHz

108.000-179.995 and 320.000-349.995MHz

400.000-479.995MHz and 700-985MHz

TX26.000-29.995MHz and 50.000-53.995MHz

136.000-174.995MHz and 400.000-479.995MHz

Memory channels

999

Frequency step

5/6.25/10/12.5/20/25/30/50/100kHz

Work mode

F2D/F3E

Operating temperature

-20°C-+40°C

Antenna impedance

50ohm

Power requirement

13.8VDC±15%

Weight

1260g (Mobile/Base transceiver)

Dimension

190x140x44 mm(Mobile/Base transceiver)

Main Function
1. Full Duplex Cross-band repeater
2. Both Stations can Form Combined Same or Different Band (s) Repeat
3. Full Duplex Working Mode on A/B Areas (e.g: A area transmitting and B area receiving at the same time, vice versa)
4. Dual Speaker & Dual Output
5. Same or Different Band (s) Simultaneous Reception UU.W.UV or VU
6. Frequency Range Suitable for any Region of any Country:
RX: 26.000-29.995MHz & 50.000-53.995MHz
108.000-179.995MHz & 320.000-349 .995MHz
400.000-479.995MHz & 700-985MHz
TX: 26.000-29.995MHz & 50.000-53.995MHz
136.000-174.995MHz & 400.000-479 .995MHz
7. Dual Display (Large LCD Dual Frequency Display, two Completely independent Operating Systems)
8. Over 999 Memory Channels (Area Scanning Management)
9. Remote-head Mounting Capacity (Multiple installation Types. Convenient Usage)
10. UV or VU Duplex Cross-band Repeat (Offset Frequency Programmable)
11. Air Band Receiving Function & AM Mode Receiving Capacity
12. High Output Power: VHF 50W. UHF 40W
13. CTCSS/DCS Encoding & Decoding. CTCSS/DCS Scanning
14. Multiple Speaker Output Settings
15. DTMF Hand Microphone with Speaker, TX/RX indicator and Volume Controller
16. Incoming (Caller) ID Display
17. DTMF Encoding & Decoding
18. Group Calls, All Calls and Selective Calls
19. 8 Groups Scrambler
20. Priority Channel Scanning
21. APO Power Management
22. Bandwidth Selectable
23 Chinese/English Voice Guide
24. Automatic Temperature Testing

25. Minimum Operating Voltage Settings
26. Stun and Kill Function
27. 2100Hz /1750Hz/1450Hz / l000Hz Single Tone Pulse Frequency (Used when activating repeater signal)
28. Three Colors Backlight Selectable
29. Remote Control Setting
30. Frequency/ Channel Scanning with CTCSS/DCS Detection
31. Multiple Cooling Ways
32 Simultaneous Scanning on AB Areas

Package

1 x Mobile/Base transceiver

1 x Hand microphone

1 x Inclined switchboard panel

1 x Screw sets

1 x Hand microphone hook

1 x Mobile mounting bracket

1 x Mobile power cord

1 x Extension cable

1 x Use´s manual

Produktgalleri



IMAGE COMING SOON!