PVA vannløselig filament - til support



Produktkode: 398aa
Tilgjengelighet: Opp til 1 mnd leveringstid
Weight: 500.00g

Pris: kr. 450,00

Kort beskrivelse
SUN PVA 1.75mm 3D Printer Filament 0.5kg 1.1lb Water-soluble Consumables Refill

Beskrivelse
Dette filamentet kan brukes til stilasstøtte for PLA-printing for kompliserte strukturer der støttekonstruksjoner kreves.
Filamentet kan etter printingen fjernes med vann slik at dent originale objektet kommer fram.

Features:
Work as a supporting material for PLA and some other materials, but not for ABS.
0.5KG net (approximately 1.1lbs) filament with black spool.
eSUN PVA 3D printer filament vacuumed sealed with desiccant.
1.75mm filament diameter (dimensional accuracy +/- 0.05mm)
Recommended extrusion/nozzle temperature 190°C - 220°C

Specifications:
Brand: eSUN
Color: Natural
Material: Water-soluble Material
Filament Diameter: 1.75mm
Dimensional Accuracy: +/- 0.05mm
Extrusion Temperature Range: 190 Celsius to 220 Celsius
Bad Temperature: No Heat/60°C-80°C
Net Weight: 0.5kg/1.1lbs

PVA Advantages:
PVA is a support material. Typically it is used with PLA filament. PVA is best printed around 195 Celsius.
When a PLA product is printed out, it can be thrown into water so that PVA supporting material can be melted away. Cold water would take 4 hours to melt all PVA. , Warmer water will melt PVA faster.
PVA is soft, soluble in water under normal temperature.

Packing List: OS1301
1 x 3D Printer Filament
If you have any questions, please feel free to contact us.

Produktgalleri

